



Overview

SolarSpan's low heat ultraslim 9W LED downlight has been custom designed for Bondor insulated roof products and outdoor use in patios and pergola applications. Our 9W LED Downlight provides an energy efficient lighting solution with up to 50,000 hours of operational use and covered by a 3 year manufacturer's return to base warranty.

Domestic

- Kitchens
- Bathrooms
- Laundries
- U/cover areas
- Eaves
- Soffits

Commercial

- Storage areas
- Toilets
- U/cover areas
- Eaves
- Shops, malls
- Soffits

Industrial

- Task lighting
- Toilets
- Amenities

Kit Contains

- 1 x 9W LED Downlight
- 1 x 9W Driver
- 2 x DC extension lead 6m
- 1 x Trim white (fitted)
- 1 x Trim brushed chrome (optional)



Features


Input Power	9 W	
Input Voltage	Non-Dimmable	100 - 240 VAC 50/60 Hz
	Dimmable	220 - 240 VAC 50/60 Hz
LED Current	350 mA	
Colour Rendering Index	> 80	
LED Diameter	110mm	
LED Depth	24mm	
Lumens per Watt	81 lm / W	
Colour Appearance	Warm White	Cool White
Lumen Output	730 lm ± 5%	800 lm ± 5%
Colour Temperature	3000 K	4000 K

Call 1800 763 707 or visit www.solarspan.com.au

Manufactured under ISO 9001: 2008 to standards:

AS/NZS60598.1
AS/NZS60598.2.1

AS/NZS60598.2.2
AS/NZS CISPR 15



Characteristics and specifications may change without notice. All electrical installations / connections should be carried out by a competent person at all times. Application images are indicative only and may not contain actual product. The information contained in this publication is typical and must not be interpreted as a guarantee of individual product performance. Metecno Pty Limited. ABN 44 096 402 934. The manufacturer reserves the right to change the specification without notice. Bondor[®], SolarSpan[®] and InsulRoof[®] are trademarks of Metecno Pty Limited. BlueScope, COLORBOND[®] and colour names are trademarks of BlueScope Steel Limited. The colours shown in this publication have been reproduced to represent actual product colours as accurately as possible. However, given printing limitations, we recommend checking your chosen colour against an actual sample before placing orders. This advice is of a general nature only. Designers must provide for adequate structural performance and other Building Code requirements. This information is subject to change. Refer to Bondor[®] website for latest version. Consult Bondor[®] for your application. BON0282 SolarSpan DL9W LED Downlight Flyer v3 - 7/12/16